



ITEM	Description	QTY
1	ST dust cover lucency	2 PCS
2	ST/PC MM simplex connector	2 PCS
3	ST boot red	1 PC
4	ST boot black	1 PC
5	Cable marker:1~2	1 PC
6	Breakout heat-shrink tubing black L=15mm	2 PCS
7	OD=2.0mm duplex OM1 62.5/125µm fiber optical cable LSZH Orange	1 PC
8	SC 2.0mm boot red	1 PC
9	SC 2.0mm boot black	1 PC
10	SC clip beige	1 PC
11	SC/PC MM simplex connector beige	2 PCS
12	SC dust cover lucency	2 PCS

ASSEMBLY CONNECTIVITY	
ST/UPC	SC/UPC
1	B
2	A

ITEM NO	LENGTH
EL2001	1.00m
EL2002	2.00m
EL2003	3.00m
EL2005	5.00m

**NOTE:**

1. Insertion loss :ST/PC<0.25dB SC/PC<0.25dB A:850&1310nm  
Return loss :ST/PC≥30dB SC/PC≥30dB A:850&1310nm

2. Durability:500 matings

3. Operation temperature:-40°C to +85°C

4. ST connector according to IEC 61754-2  
SC connector according to IEC 61754-4

**ROHS Compliant**



Designed by:	Yong Yu	Audit:	Qihua Cheng
Date:	2017/3/14	Approve:	Yong Huang
Unit:	mm	Sheet:	A4
Drawing NO:	SOP-ED-170314-11-V2		