



ITEM	Description	Q'TY
1	ST dust cover Lucency	2 PCS
2	ST/PC MM simplex connector	2 PCS
3	ST boot red	1 PC
4	ST boot black	1 PC
5	Cable marker:1~2	1 PC
6	Breakout heat-shrink tubing black L=15mm	2 PCS
7	OD=2.0mm duplex OM2 50/125um fiber optical cable LSZH Orange	1 PC
8	LC heat-shrink tubing yellow	1 PC
9	LC heat-shrink tubing white	1 PC
10	LC 2.0mm boot yellow	1 PC
11	LC 2.0mm boot white	1 PC
12	LC dip beige	1 PC
13	LC/PC MM simplex connector beige	2 PCS
14	LC dust cover white	2 PCS

ASSEMBLY	CONNECTIVITY
ST/UPC	LC/UPC
1	B
2	A

ITEM NO	LENGTH
EL7501	1.00m
EL7502	2.00m
EL7503	3.00m
EL7505	5.00m

**NOTE:**

- 1.Insertion loss :ST/PC<0.25dB LC/PC<0.25dB λ:850&1310nm  
Return loss :ST/PC≥30dB LC/PC≥30dB λ:850&1310nm
- 2.Durability:500 matings
- 3.Operation temperature:-40 °C to +85 °C
- 4.ST connector according to IEC 61754-2  
LC connector according to IEC 61754-20

**ROHS  
Compliant**

<b>ewent</b> <small>BY INVENT</small>			
Designed by:	Yong Yu	Audit:	Qihua Cheng
Date:	2017/3/14	Approve:	Yong Huang
Unit:	mm	Sheet:	A4
Drawing NO:	SOP-ED-170314-14-V2		