



ASSEMBLY CONNECTIVITY	
LC/UPC-1	LC/UPC-2
A	B
B	A

ITEM NO	LENGTH
EL9901	1.00m
EL9902	2.00m
EL9903	3.00m
EL9905	5.00m
EL9910	10.00m

NOTE:

1. Insertion loss :LC/UPC<0.25dB λ : 1310&1550nm
Return loss :LC/UPC \geq 50dB λ : 1310&1550nm
2. Durability:500 matings
3. Operation temperature:-40°C to +85°C
4. LC connector according to IEC 61754-20

**ROHS
Complaint**

LC/PC --- LC/PC DX 2.0mm G657A1 LSZH Yellow

ITEM	Description	Q'TY
1	LC dust cover white	4 PCS
2	LC/UPC SM simplex connector blue	4 PCS
3	LC clip blue	2 PCS
4	LC 2.0mm boot white	4 PCS
5	LC heat-shrink tubing white	2 PCS
6	LC heat-shrink tubing yellow	2 PCS
7	Breakout heat-shrink tubing black L=15mm	2PCS
8	OD=2.0mm duplex G657A1 9/125 fiber optical cable LSZH Yellow	1 PC

ewent
BY INVENT

Designed by:	Yong Yu	Audit:	Qihua Cheng
Date:	2017-04-10	Approve:	Yong Huang
Unit:	mm	Sheet:	A4
Drawing NO:	SOP-ED-170410-02-V2		